


# MAF400 series

AIR UNITS (Filter)



Symbol:



## Specification:

Model	MAF400		
Bore No.	8A	10A	15A
Port size	PT 1/4	PT 3/8	PT 1/2
Medium	Air		
Operating pressure range	0~9.9 kgf/cm <sup>2</sup> (0~0.99 MPa)		
Proof pressure	15 kgf/cm <sup>2</sup> (1.5 MPa)		
Ambient temperature	-5~+60°C (No freezing)		
Filter element	Standard: 40 μm Option: 5 μm		
Max. flow rate (※) $\ell$ /min	1500	2000	2200
Option	Bracket		
Weight	550 g		

※ Flow is at pressure  $P=7$  kgf/cm<sup>2</sup> with pressure drop  $\Delta P=0.3$  kgf/cm<sup>2</sup>. (ANR)

## Order example:

MAF400 - 8A - □ - □ - B - BSP

MODEL

BORE SIZE

8A: PT 1/4  
10A: PT 3/8  
15A: PT 1/2

FILTER ELEMENT  
Blank: 40 μm  
5u: 5 μm

D: auto drain valve  
(FMRF 300)

Bracket

PORT THREAD  
Blank: PT thread  
BSP: BSP thread  
NPT: NPT thread

